

Ultimate Floor Defense

To the

BREAKTHROUGH HIGH GLOSS FLOOR CARE

CLEANBOSSPRO.COM

Finally, You Can Have Glossy, Shiny Floors Without Odors or Heavy Metals

CleanBoss Cleaner Cleaner High Gloss Universal Floor Finish creates a new standard in floor care by combining an unequaled level of environmental preference with performance, which surpasses conventional floor finish technology. Excels with all maintenance systems: scrub and recoat, spray buff or burnish. You'll get a tough, black-mark resistant shine with no powdering. No sealer is required on resilient flooring, even after heavy stripping. **Use on vinyl, laminate, linoleum, rubber, brick, stone, terrazzo, and bamboo floors.**

Benefits

- NEUTRAL PH
- NO SUSPECTED ENDOCRINE DISRUPTORS
- NO HEAVY METAL COMPLEXES
- NO APE'S
- NO FORMALDEHYDE
- NO ODOR
- PHTHALATE FREE

Properties	
Color	Opaque, White
Fragrance	No Odor
Viscocity	<10
VOC's (% by weight) EPA Method 24	.112%
рН	7.95
Readily Biodegradable	Yes
Phosphate Free	No

Available Packages

2x2.5 gal (2x9.5 litre) case

4x1 gallon (4x3.8 litre) case

Directions for Use

Floor preparation: For best results, start with a properly prepared floor by removing all of the old finish using CleanBoss Clean Cleaner High Gloss Universal Floor Stripper according to its directions. Rinse floor thoroughly to remove all residues and allow to dry.

Application:

Do not apply product if flooring and/or ambient temperatures are less than 55°F (13°C).

 If not sealed, build an adequate base for ease of maintenance with the desired floor care system by applying three (3) thin coats care system by applying three (3) thin coats. Allow adequate drying time between coats, typically 75°F (24°C) and 50% relative humidity requires an average of 15 minutes. Adjust drying times according to specific application conditions.

 2. For added depth of gloss and protection, apply an additional two (2) thin coats may be applied. If applying thick coats allow 24-48 hours dry time before applying.

Maintenance:

CleanBoss Clean Cleaner High Gloss Universal Floor Finish is an environmentally preferable zinc-free coating that may be

Coverage: 3000-4000 sq ft per gallon/280-370 sq m per 3.8 litres.

Slip Resistance: Meets ASTM D2047-93 requirements for slip resistance.

For a more detailed application and maintenance program please ask for our Step by Step Green Procedures Guide - Form 4105.

For handling and precautionary information, reference the product label and safety data sheet.

attacked or dulled by harsh cleaners.

 Daily dust mopping or sweeping will remove abrasive debris that will impact appearance and increase maintenance.
Damp mop or autoscrub using 1/2 oz per gallon/15 ml per 3.8 litres of CleanBoss Clean Cleaner Floor & Surface.

 Recommend using aqua pad with burnishing machine, for gloss restoration.
<u>Deep-scrub as required to maintain finish</u>

and gloss.

